



# Instructions: Medlin Yard Ramp Landing Gear Installation

**PRINT  
THIS  
PAGE**

**If you need assistance, please contact one of us:**

- Jim Kunze, The Yard Ramp Guy at 630-235-8586 (Cell)
- Jeff Mann, The Yard Ramp Guy at 847-770-1360 (Cell)
- Mark Medlin, Medlin Equipment at 877-463-3546



## STEP #1

Set ramp entrance on the ground.

Lift the 6' level off to 35" high from ground to bottom of curb (curb is the 12" channel).



## STEP #2

Install one landing gear leg (leg without the crank handle).

Please note the legs are set at a perfect match to allow ramp to rise and lower at same time.

Do not un-crank the legs from their position during install.

Tighten all 4 bolts



## STEP #3

Install outer gusset. Top bolts are shorter and provided on gusset already.

Tighten all 4 bolts.

Install inner gusset.  
Tight all 4 bolts



## STEP #4

Install cross tube to landing gear leg.

Must install other end at same time of installing next landing gear leg.

Please note cross bar cannot be connected after both landing gear leg are installed.

## STEP #5

Install next landing gear leg (this leg has the crank handle). Tighten all 4 bolts

Install outer gusset. Top bolts are shorter and provided on gusset already. Tighten all 4 bolts.

Install inner gusset.  
Tighten all 4 bolts



## STEP #6

After landing gear system is installed and completely secured, raise 6' level off end to 42" high from ground to bottom of curb.

Lower wheels onto ground with crank handle

Install Tow Boot and begin using your ramp.